

FEATURES

- ✓ High energy performance with low heat generation and safe operation
- ✓ Active voltage balancing system
- ✓ Temperature control

APPLICATIONS

- ✓ Energy harvesting and recovery systems for heavy duty applications
- ✓ Wind turbine pitch control
- ✓ UPS systems
- ✓ Micro Grid



SPECIFICATIONS

ELECTRICAL PARAMETERS		
Rated Voltage, V_r		16 V
Maximum Voltage ¹		18 V
Rated Capacitance ²		500 F
Capacitance Tolerance		-0% + 20%
Maximum ESR DC	Maxwell Technologies Test Procedure ³	2.1 mOhm
	Nesscap Co. Test Procedure ⁴	1.8 mOhm
Typical ESR DC	Maxwell Technologies Test Procedure ³	1.6 mOhm
	Nesscap Co. Test Procedure ⁴	1.0 mOhm
Test Current for Capacitance and ESR_{DC}		100 A
Maximum Peak Current, 1 second (non repetitive) ⁵		1950 A
Leakage Current, maximum ⁶ (passive voltage balancing system)		6 mA

YUNASKO 2016. Version 0516. All rights reserved. Specifications are subject to change without notice.

POWER AND ENERGY

Specific Energy, E_{\max}^7		3.3 Wh/kg
Stored Energy ⁸		17.8 Wh
Usable Specific Power, P_d^9	Maxwell Technologies Test Procedure ³	2.8 kW/kg
	Nesscap Co. Test Procedure ⁴	3.3 kW/kg
Maximum Specific Power (matched impedance), P_{\max}^{10}	Maxwell Technologies Test Procedure ³	5.9 kW/kg
	Nesscap Co. Test Procedure ⁴	6.8 kW/kg

TEMPERATURE

Operating Temperature (ambient temperature)		
Maximum		+65 °C
Minimum		-40 °C
Storage Temperature (stored discharged)		
Maximum		+70 °C
Minimum		-40 °C

LIFE TEST

Capacitance Change (% decrease from minimum initial value)	20%
ESR Change (% increase from maximum initial value)	100%

LIFE

High Temperature (at Rated Voltage and Maximum Operating Temperature)	1500 hours
Room Temperature (projected life at Rated Voltage and 25°C)	10 years
Cycle Life (Rated Voltage – Half Voltage, Test Current – 100A, at 25°C)	1 000 000 cycles
Shelf Life (stored discharged up to a Maximum Storage Temperature)	4 years

SAFETY

Short Circuit Current, typical (maximum current if shorted at Rated Voltage. Do not use as an operating current)	10 000 A
Highpot Test	2500 V DC

BALANCING SYSTEM / TEMPERATURE CONTROL


Internal Temperature Sensor	NTC Thermistor
Temperature Interface	Analog
Cell Voltage Monitoring	Overvoltage Alarm
Connector	SAL-8-FK3-0,2
Adapter	SAL-8-FK3 to Deutsch DTM04-4P
Cell Voltage Management	Active Voltage Balancing System

PHYSICAL PARAMETERS

Power Terminals	M8/M10
Recommended Torque – Terminals	20/30 Nm
Cooling	Natural Air Convection
Mass	5.2 kg

MODULE DIMENSIONS

L_{max} , mm	H_{max} , mm	W_{max} , mm
414	184	63



YUNASKO 2016. Version 0516. All rights reserved. Specifications are subject to change without notice.

NOTES:

The technology is protected by a number of patents and patent applications.

Module dimensions are for reference only and can be changed to meet the customer requirements.

1. Maximum voltage non-repeated, not to exceed 5 seconds.
2. Capacitance measured at 25 °C as per IEC 62391-1.
3. ESR_{DC} measured at 25 °C as per Maxwell Technologies test procedure specified in the 16V 500F module (BMOD0500 P016 B01) datasheet, document #1009363.10. Document available at www.maxwell.com.
4. ESR_{DC} measured at 25 °C as per Nesscap Co. test procedure specified in the 16V 500F module (EMHSR-0500C0-016R05) datasheet, document # 20151105 Rev.1. Document available at www.nesscap.com.
5. Maximum peak current (discharge from V_r to $V_r/2$ per 1 second):

$$I_{\max} = \frac{CV_r}{2(C \times ESR_{DC} + 1)}$$

6. After 72 hours at 20 °C and rated voltage as per IEC 62391-1. Initial leakage current can be higher.

$$7. E_{\max} = \frac{CV^2}{2 \times 3600 \times mass}$$

$$8. E_{\text{stored}} = \frac{CV^2}{2 \times 3600}$$

$$9. \text{As per IEC 62391-2: } P_d = \frac{0.12V^2}{ESR_{DC} \times mass}$$

$$10. P_{\max} = \frac{0.25V^2}{ESR_{DC} \times mass}$$

YUNASKO 2016. Version 0516. All rights reserved. Specifications are subject to change without notice.